



















Fästmaterial

Användning	Typ av fästdon	Beskrivning	Förpackning												
		Ö 48 Dim. 4,8 x 19 mm Borrk. 4 x 0,5 mm	250 st/förp.												
		L 48 Dim. 4,8 x 20 mm Borrk. 1- 4 mm	250 st/förp.												
		L 55 Dim. 5,5 x 25 mm Borrk. 1,5- 5 mm	250 st/förp.												
		T 48 Dim. 4,8 x 35 mm Borrk. 3 x 0,5 mm	250 st/förp.												
		B 55 Dim. 5,5 x 32 mm Borrk. 4 - 12 mm	250 st/förp.												
		B 63 Dim. 6,3 x 25 mm Borrk. 2 - 6 mm (2 x 3,0 mm)	250 st/förp.												
		KSAB Dim. 6,3 x 19 mm Ej självborrande	250 st/förp.												
		Ö 63 Dim. 6,3 x 22 mm, fast bricka Borrk. 4 x 0,75 mm	250 st/förp.												
		Trycktät popnit <table border="1"> <thead> <tr> <th>Diameter</th> <th colspan="2">Maxgrepp</th> </tr> </thead> <tbody> <tr> <td>AD 48</td> <td>3,2 mm</td> <td>6,5 mm</td> </tr> <tr> <td>AD 56</td> <td>4,0 mm</td> <td>5,0 mm</td> </tr> <tr> <td>AD 66</td> <td>4,8 mm</td> <td>5,0 mm</td> </tr> </tbody> </table>	Diameter	Maxgrepp		AD 48	3,2 mm	6,5 mm	AD 56	4,0 mm	5,0 mm	AD 66	4,8 mm	5,0 mm	1000 st/förp.
Diameter	Maxgrepp														
AD 48	3,2 mm	6,5 mm													
AD 56	4,0 mm	5,0 mm													
AD 66	4,8 mm	5,0 mm													